

P/N	HOSE OD { INCHES }	HOSE OD MM	Max OD	GRIP LENGTH	EYE LENGTH	TOTAL LENGTH	NUMBER OF PLYS	APPROX WEIGHT	AVERAGE BREAKING STRENGTH
3/8"	5/16" - 1/2"	8-14 MM	.70"	12.5	4	16.5	8X3	1/4 LB	4200LBS
1/2"	1/2" - 3/4"	14-20 MM	.85"	18	4.5	22.5	8X3	1/4 LB	4200LBS
7/8"	3/4" - 1.1/8"	20-30 MM	1.4"	20	6	26	12X2	3/4 LB	6200LBS
1"	1.1/8" - 1.1/2"	30-40 MM	2"	27	8	35	12X2	1 LB	12000Lbs
1.1/4"	1.1/2" - 1.7/8"	40-50 MM	2.5"	32	8	40	12X2	1.1/4 LB	12000Lbs
1.1/2"	1.7/8" - 2.3/8"	50-60 MM	3"	41	11	52	12X2	2.1/4 LBS	17000 Lbs
2"	2.3/8" - 2.3/4"	60-70 MM	3"	43	11	54	12X2	2.1/2 LBS	17000 Lbs
2.1/2"	2.3/4" - 3.3/8"	70-85 MM	3.75"	43	13	56	12X2	5.1/4 LBS	17000 Lbs. 1/8" Wire 27,000
3"	3.3/8" - 3.7/8"	85-100 MM	4"	58	17	75	12X2	5.1/4 LBS	26000LBS
3.1/2"	3.7/8" - 4.3/4"	100-120 MM	4.5"	58	19	77	12X2	5.1/2 LBS	26000LBS
4"	4.3/4" - 5.1/2"	120-140 MM	6.25"	71	19	90	16X2	7.1/2 LBS	30000LBS
6"	5.1/2" - 7"	140-180 MM	8"	79	19	98	16X2	8 LBS	30000LBS